

# AGILIOS™ - coiler AR90II up to 90m

Coiler for the push camera inspection system AGILIOS™, version AR90II. It is used for inspections of property drainage systems and their connecting pipes leading to the main sewer but also for the inspection of main sewer pipes. Due to its extremely robust and splash proof construction the coiler is eminently suitable for the use under harsh conditions and in all weathers. The maximum length of the rod is 90 m.

## TECHNICAL DATA - AR90II

|   |                        |
|---|------------------------|
| Drive                                   | manual (push rod)      |
| Cable-length                            | 30 / 60 / 90 m         |
| Meter counter                           | 1                      |
| Voltage                                 | 14.4 V DC              |
| Exchangeable battery                    | yes                    |
| Battery type                            | Li-ion                 |
| Battery life                            | approx. 2h / battery   |
| Battery capacity                        | 4 Ah / battery         |
| Interfaces                              | 1 x Video OUT (analog) |
| Ambient temperature range               | 0 °C - 40 °C           |
| Storage temperature range               | 0 °C - 40 °C           |
| Material (frame / basket)               | aluminum / plastic     |
| Dimensions (W x H x D)                  | 430 x 780 x 700mm      |
| Weight<br>(incl. 60 m rod, 2 batteries) | approx. 24 kg          |



- Extremely robust and splash-proof for the use under harsh conditions
- Easy transport through large all-terrain wheels
- Space-saving storage through removable wheels
- Operation in vertical and horizontal position of the coiler possible
- Portable use through battery operation
- Integrated racks for two exchange batteries
- Automatic switching from battery 1 to battery 2
- Battery charging via external charging station
- Mains operation (optional) possible
- Extremely robust, yet flexible push rod
- Meter counter
- Analog Video OUT interface
- Reel brake
- Rotatable and pivoting control panel mounting for flexible adjustment of the control panels
- Reflectors for greater visibility for inspection work in nocturnal traffic
- Compatible with the control panels VC200 and VC50



**iPEK International GmbH** · See, Gewerbepark 22 · 87477 Sulzberg · GERMANY

☎ +49 8376 921 800 📠 +49 8376 921 8021 ✉ isg\_info@idexcorp.com 🌐 www.ipek.at

---

Issue: July 2015 – subject to changes.